


MAPS™ HD - High-Density RTP Traffic Generator for IP & Wireless Networks

MAPS™ RTP High Density Call Generator
(SIP, SIP I, luCS, GSMA, BICC, MEGACO, MGCP, S1AP)

MAPS™ RTP High Density Call Generator
(SIP, SIP I, luCS, GSMA, BICC, MEGACO, MGCP, S1AP)



Overview

MAPS™ (Message Automation and Protocol Simulation) is GL's standard framework for emulation of IP, TDM, and Wireless protocols. GL's **MAPS™ HD**, is an advanced bulk RTP traffic generator used to emulate high volume calls with RTP traffic. It is available as special purpose rackmount/lunchbox network appliance w/ 4x1GigE or 8x1GigE network interface cards capable of high call intensity (hundreds of calls/sec) and high volume of sustained calls (tens of thousands of simultaneous calls/ platform).

The network appliance performs signaling and traffic generation for a vast array of communication protocols covering IP and Wireless networks. With additional licensing, MAPS™ HD RTP can support emulation of SIP (PKS120), GSM A (PKS137), BICC (PKS155), MGCP, H.248/MEGACO (PKS122), and provides non-reference based voice quality using E-model (R-factor) and MOS with five mapping scales.

MAPS™ HD network appliance is designed to easily achieve up to 64,000 simultaneous calls per appliance (i.e. 8000 RTP media sessions per port). Using a stack of multiple servers, a larger test system with 100K-200K calls is achievable for enterprise to carrier grade testing.

The network appliance provides a modular and flexible solution to generate real voice calls using industry standard voice codecs such as G.711 A/μ-law, G.722, G.722.2 (AMR-WB), G.722.1, G.726, G.729A/B, GSM (EFR, FR and HR), AMR (Narrowband and Wideband), EVRC, EVRCB, EVRC-C, iLBC, Speex, SpeexWB, EVS, OPUS and RFC 2833/4733-out of band events.

For more details, refer to [High-Density Call Generator for IP & Wireless Networks](#).



GL Communications Inc.

818 West Diamond Avenue - Third Floor, Gaithersburg, MD 20878, U.S.A

(Web) www.gl.com - (V) +1-301-670-4784 (F) +1-301-670-9187 - (E-Mail) info@gl.com

Features

HD Characteristics

- Signaling calls can be transmitted over UDP and TCP, IPv4 and IPv6, and TLS for secure transport
- RTP media is transmitted over UDP with IPv4 or IPv6 address
- Unique endpoint emulation using IP address, MAC address, and VLAN tagging
- For UDP transport, scales up to 64,000 simultaneous calls for each appliance (i.e. 8,000 RTP media sessions per port) with duplex RTP traffic
- Achieve up to 250 calls per second (with RTP traffic)
- Emulates around 50,000 to 100,000 user endpoints.
- Manage 10+ MAPS™ systems with single point of control from Master Controller
- Simulate various traffic conditions to measure the performance of a network element
- Simulate complete protocol state machine to troubleshoot the network issues
- Powerful Load Generation, Scheduler, and Command Line Interface (CLI) for automation, remote control, and load testing
- Configurations, test scripts, and profiles can be saved and reused on a different systems
- Easy-to-use scripting interface for creating test scripts
- User can modify signaling messages, message parameters, and/or information elements
- Packet level fault insertion
- Real-time monitoring and reporting of registration and call statistics
- Statistics can be viewed on any pair of endpoints
- Export data to other applications for customized user report

Traffic Types

- Capability to generate more than 500 simultaneous video calls on a Core i7 systems.
- Simulation of [RTP Traffic](#) such as voice files, single or dual tones, FAX, Dynamic VF, and Impairments
- All Voice Codecs supported including –
 - G711 μ -law and A-law with VAD
 - GSM-FR, HR, EFR
 - G729A, G729B, G722, G722.1
 - G726 (40K, 32K, 24K, 16K) with VAD
 - AMR (codec rates-4.75, 5.15, 5.9, 6.7, 7.4, 7.95, 10.2, 12.2) with VAD (requires additional licenses)
 - AMR-WB (Codec rates-6.60 kbps, 8.85 kbps, 12.65 kbps, 14.25 kbps, 15.85 kbps, 18.25 kbps, 19.85 kbps, 23.05 kbps, 23.85 kbps) with VAD (requires additional licenses)
 - EVRC, EVRCB, EVRC-C (requires additional licenses)
 - SMV, SPEEX, SPEEX-WB, ILBC
- Generation of [RTP Video Traffic](#) (with H.264, H.263, and VP8 video codecs)
- RTP Voice Quality Measurements – MOS, R-Factor scores
- Generation of [RTP FAX Traffic](#) - G.711 Pass-through and T.38 UDPTL

Test Bed Configuration

The configuration window allows users to setup the required test environment to emulate messaging from different SIP entities such as the User Agent Client (MAPS™) - to - User Agent Server (MAPS™).

MAPS™ HD testbed includes local IP addresses configured to Normal NIC for SIP Signaling, and 4 RTP cores for traffic management between MAPS™ SIP HD and RTP core. Each RTP core uses one port on the GL's HD Interface for sending and receiving RTP traffic.




Figure: Testbed Setup Configuration

Bulk Video Call Simulation

[MAPS™ SIP](#) provides the Bulk Video Call Simulation capability using its pre-recorded video traces supporting codecs like H.264, H.263 etc. On a high-performance computing platform (core-i7), it is possible to generate more than 500 simultaneous video calls. With a [High Density \(MAPS™ HD\)](#) platform, it is possible to achieve much more capacity.




Figure: Bulk Video Call Simulation in MAPS™ SIP

Bulk RTP Voice Simulation

RTP allows to generate and to receive voice traffic over IP networks. Transmit and Receive pre-recorded Voice Files in wave, pcm, and GL's proprietary pre-compressed GLW files with a synchronous Tx/Rx option. You can also directly send live voice using Talk using Microphone feature, and play the recorded voice files directly on to PC speakers. Some additional features that help in the voice traffic simulation are listed below-

- Allows to specify a desired voice payload type to each codec for sending and receiving payload;
- Sampling rate of the codec is displayed for the selected codec.
- Comfort noise generation is supported for A-law, μ -law and G.726 codecs for sending and receiving payload.
- Allows to set the buffer used for delayed packets that arrive at receiving end (both static and dynamic jitter buffers are supported)
- Allows to set QoS (Type of Service) properties such as precedence, delay, throughput and reliability values to the outgoing stream
- Customize codec options (payload type,ptime) over Tx/Rx sessions. All Voice Codecs are supported (Visit [Voice Codecs](#) webpage for more comprehensive information)




Figure: Bulk RTP Voice Simulation

Digits, and Tones, and Impairments Options in RTP Traffic

- RTP allows to generate and to receive RTP traffic over created sessions (RFC3550). Different RTCP packets are also generated at random intervals carrying control information about the session.
In-band Digit transmission & detection (DTMF and MF digits)
- Out-band Digit transmission & detection (all events defined as per RFC2833 and RFC4733)
- Tone transmission & detection (single, dual and user defined tones)
- Loopback traffic

Users can introduce various impairments on outgoing RTP streams. The supported impairment types includes Latency, Packet Loss, and Duplicate Packets and Out of sequence Packets.

Load Generation

The Load Generation feature allows bulk call configuration, which includes Total Calls to generate, and Maximum Active Calls, Max/Min Call rate, Start Call Rate, and Maximum Call Rate parameters.

Sip Call Control script which can handle SIP signaling and traffic is loaded along with the profiles configured for each HD port.

MAPS™ SIP uses 4 ports on GL's HD card to generate and receive RTP packets. Maximum supported simultaneous calls on each port is 5000.




Figure: Load Generation

QoS Statistics

The QoS Statistics for each port is calculated for the received traffic for every specified number of sessions in RTPConfig.ini configuration file.




Figure: QoS Statistics

Statistics

Statistics feature provides both the Call Statistics and Message Statistics with the pie graph indicating the Pass/Fail Call Ratio. By default, all call handling scripts are assessed by MAPS™ to provide statistical information.

The statistical distribution of number of calls per second (time) and total number of simultaneous calls per second is also plotted for the statistics log as per the pattern configured in Load Generation.



Figure: Call and Message Statistics

MAPS™ HD Appliance



Figure: MAPS™ HD Appliance (Lunchbox PC)

MAPS™ HD Appliance (Contd.)



**8x1GigE
High Performance Smart NIC**

Figure: MAPS™ HD Appliance (Rack PC)

MAPS™ HD System Setup

The 2 regular PC NICs are connected to a managed switch using Ethernet cables as shown below. The four ports on GL's HD NIC card are connected to a Device Under Test (DUT).




Figure: MAPS™ HD System Setup

Buyer's Guide

| Item No | Product Description |
|------------------------|--------------------------------------------------------------------------------|
| PKS109 | MAPS™ HD (requires GL's high interface NIC) |
| PKS102 | RTP Soft Core for RTP Traffic Generation |
| PKS120 | MAPS™ SIP |
| PKV100 | PacketScan™ |
| PKV120 | PacketScan™ HD (4 x 1GigE) |
| PKV122 | PacketScan™ HD (2 x 10 GigE) |
| PKV121 | PacketScan™ FB |
| PKS106 | RTP Video Traffic Generation |
| PKS103 | RTP luUP Softcore |
| PKS107 | RTP EUROCAE ED137 |
| PKS108 | RTP Voice Quality Measurements |
| PKS200 | RTP Pass Through Fax Emulation, requires one of the licenses below, (w/dongle) |
| PKS202 | 2 Fax Ports, RO |
| PKS203 | 8 Fax Ports, RO |
| PKS204 | 30 Fax Ports, RO |
| PKS205 | 60 Fax Ports, RO |
| PKS206 | 120 Fax Ports, RO |
| PCD103 | AMR codec for MAPS™ |
| PCD104 | EVRC codec for MAPS™ |
| PCD105 | EVR_B codec for MAPS™ |
| PCD106 | EVR_C codec for MAPS™ |

For more details, refer to [Signaling and Traffic Simulator](#) webpage.



GL Communications Inc.

818 West Diamond Avenue - Third Floor, Gaithersburg, MD 20878, U.S.A
 (Web) www.gl.com - (V) +1-301-670-4784 (F) +1-301-670-9187 - (E-Mail) info@gl.com